

M A T E R I A L S A F E T Y D A T A S H E E T

Page 1

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2712

PRODUCT NAME: WINDSHIELD WASHER SOLVENT

H M I S C O D E S : H C F R P

PRODUCT CODE: 2712

3 3 0 B

W H M I S C L A S S :

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International

ADDRESS : 1401 Barclay Circle
 Marietta, GA 30060

INFORMATION PHONE : (770)424-7550

DATE PRINTED: 04/05/2011

PREPARED BY: Allen Buckalew, TECHNICAL SERVICES

REVISION DATE: 04/05/2011

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS

	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
*Methanol	67-56-1	200ppm	200ppm	50-55%

* Indicates toxic chemical subject to the reporting requirements of SARA Title III, Sec. 313

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	147 F	SPECIFIC GRAVITY (H2O=1):	0.91
VAPOR DENSITY:	ND	EVAPORATION RATE:	ND
DENSITY:	7.59 lb/gl	MATERIAL V.O.C.:	50-55% by weight
SOLUBILITY IN WATER:	COMPLETELY SOLUBLE.	pH (Concentrate):	7.5
APPEARANCE:	BLUE CLEAR LIQUID	pH (Diluted):	ND
ODOR:	SLIGHT ALCOHOL AROMA.		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IC

FLASH POINT: 71 F

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 6.0%

UPPER: 36%

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in containers rupturing. Use self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2712

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, strong oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause nose, throat, and lung irritation. Nausea, vomiting, blurred vision.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Symptoms may parallel inhalation overexposure.

INGESTION: Toxic. Can cause blindness or death if swallowed.

CHRONIC EFFECTS OF OVEREXPOSURE: Marked impairment of vision has been reported. May cause skin irritation.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

INGESTION: IF SWALLOWED: Call a physician immediately. Induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2712

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 100 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat. Store only in a cool dry area.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None needed unless ventilation is not adequate to reduce vapors below TLV levels. If needed, use a NIOSH approved respirator with an organic vapor cartridge.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Consumer Commodity

DOT HAZARD CLASS: NA

UN NUMBER: NA

DOT PACKING GROUP: NA

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.