

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

REPELL
DA617

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

REPELL
DA6171

MANUFACTURED FOR:
Drummond American Corporation
600 Corporate Woods Pkwy.
Vernon Hills, Illinois 60061

IN CASE OF EMERGENCY CALL:
ROCKY MOUNTAIN POISON & DRUG CENTE
COLLECT AT: (303) 623-5716

DATE OF PREPARATION:
03/01/94

INFORMATION TELEPHONE NUMBER:
(708) 913-9313

SECTION I - IDENTITY

PRODUCT NUMBER DA6171
PRODUCT NAME REPELL
PRODUCT CLASS SOLVENTS

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENT	CAS NUMBER	%	ACGIH TLV PPM	MG/ M ³	PEL PPM	STEL PPM
PETROLEUM DISTILLATE	5-20					
PETROLEUM OIL MIXTURE	5-20					
TRICHLOROETHYLENE *	79-01-6	30-70				
* THIS CHEMICAL IS SUBJECT TO S.A.R.A. TITLE III SECTION 313 REPORTING	5			ND	5.00	1
	50			269.0	50.00	200.1

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (degrees F): N/A
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Slower than ether.
PERCENT VOLATILE (By weight): N/A
WEIGHT PER GALLON (LBS): N/A
OPTIONAL INFORMATION:
Appearance/Odor: Clear brown liquid having a sweet odor.
Specific Gravity (Water=1): 0.89
Vapor Pressure (MMHG): 41
Solubility in Water: Negligible
Evaporation Rate (Butyl Acetate=1): >1

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:
OSHA CLASS
DOT CLASS ORM
FLASH POINT: N/A

U.N. CLASSIFICATION:
PER DOT
PER IMCO

LEL: 2.0
UEL: 12.0

METHOD: Tag Open Cup

AEROSOL PRODUCT: Treat as cylinder of compressed gas.

EXTINGUISHING MEDIA:

FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

At elevated temperatures (over 130 degrees Fahrenheit) containers may vent, rupture or burst.

SPECIAL FIREFIGHTING PROCEDURES:

Keep containers cool. Use shielding to protect personnel against bursting, rupturing or venting containers.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

Hydrogen chloride, oxides of carbon and minute traces of phosgene and chlorine, formed upon combustion.

CONDITIONS TO AVOID:

Avoid heating to abnormal temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID):

Oxidizing agents.

D.O.T. EMERGENCY RESPONSE INFORMATION:

NOT APPLICABLE

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

REPELL
DA6171

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Inhalation may cause irritation of the respiratory tract, dizziness, nausea, loss of equilibrium. Chronic inhalation can result in damage to the liver and kidneys. Swallowing of the materials may result in irritation of the mouth and GI Tract.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION

MEDICAL CONDITIONS PRONE TO OVEREXPOSURE:

Irritating skin or eye disorders may be aggravated by exposure to this product.

TARGET ORGANS AFFECTED:

Liver, Kidneys.

CARCINOGENICITY:

None of the components in this chemical are listed by IARC, NTP or OSHA as a carcinogen.

EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention if irritation persists. Skin Contact: Remove contaminated clothing. Flush skin with water, follow by washing with soap and water. Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. If ingested seek a physician.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Provide ventilation. Remove sources of flame, spark or heat. Wipe up spills, then wash with a cleaner to remove final traces.

WASTE DISPOSAL METHOD:

Dispose of product in accordance with local, county, state, and federal regulations. Do not puncture or incinerate container. Do not reuse container. Wrap container and place in trash collection.

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

REPELL
DA6171

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

VENTILATION:

LOCAL EXHAUST: Hood or fan

MECHANICAL: Maintain adequate ventilation

PROTECTIVE GLOVES:

WEAR GLOVES KNOWN TO BE IMPERVIOUS TO THE INGREDIENTS FOUND IN THIS PRODUCT.

EYE PROTECTION:

SAFETY GLASSES OR GOGGLES ARE RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

Wear impervious clothing to prevent skin contact.

HYGIENIC PRACTICES:

Wash hands before eating or using the washroom. Smoke ---
in SMOKING AREAS O N L Y .

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at room temperatures above 130F.

OTHER PRECAUTIONS:

Please read and follow directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

SECTION X - OTHER INFORMATION

----NTPA INDEX----

PREPARED BY:

HEALTH 3
FLAMMABILITY 0
REACTIVITY 1
Tlv Threshold Limit Value
PEL Permissible Exposure Level
NTPA National Fire Protection Association
CAS Chemical Abstract Service
NTP National Toxicology Program
OSHA Occupational Safety and Health Admin.
IARC International Agency for Research on Cancer

NO NO DATE
LEI Lower Explosive Level
NE Not Established
PPM Parts Per Million
D.O.T. Department of Transportation
N/A Not Applicable
M3 Approximate milligrams per cubic meter of air

---NTPA HAZARD INDEX---
SEVERE HAZARD 4
SERIOUS HAZARD 3
MODERATE HAZARD 2
SLIGHT HAZARD 1
MINIMAL HAZARD 0